



Densitometers

Densitometers

DEN-1 for 0.3 - 15.0 McFarland units

DEN-1B for 0.00 - <15.00 McFarland units, powered by battery or mains

Densitometers

Compact and efficient benchtop densitometers for measuring turbidity of cell suspensions in a variety of life-science applications.

The densitometers are designed and factory calibrated to measure turbidity in the range of 0.3 to 15.0 McFarland units (DEN-1) 0.00 to <15.00 McFarland units (DEN-1B) with a small standard deviation. The densitometers can deliver a wider measurement range (up to 15.00 McFarland units) with a greater standard deviation.

Measurement range: 0.3 to 15.0 McFarland units (DEN-1), 0.00 to <15.00 McFarland units (DEN-1B)

Precision: $\pm 3\%$

Measurement time: 1 second

Standard deviation at 3.00 McFarland units: ± 0.1 McF

User calibration option

Designed for tubes with an outer diameter of 18mm. 16mm tubes can also be accommodated by using the optional tube adaptor D16 (included).

Extremely compact design with small footprint and low profile - fits easily into the smallest workspace.

DEN-1 and DEN-1B units are calibrated for operation in range 0.3-15.0 McF and 0->15.00 McF, but it is possible to measure turbidity from 0McF to 15McF. (note: the standard deviation of the values increases).



Factory calibrated - retains calibration without power supply. Can be user calibrated with commercial standards or cell suspensions prepared in the laboratory.

Bright LED display readings conveniently shown in McFarland units, are clearly visible.

Powered by 3 x AA batteries (DEN-1B only) or via external 12v power supply.





Applications

- Life-science - typical applications include determining concentration of cells (bacterial and yeast cells) in the fermentation process, detecting the susceptibility of micro-organisms to antibiotics, identifying micro-organisms with various test systems, and measuring optical density at fixed wavelength.


Densitometers

Technical specifications

			
		DEN-1	DEN-1B
		Densitometers	
Dimensions	h x d x w mm	75 x 115 x 165	
Operating temperature	°C	+4 to 40	
Light source		LED	
Wavelength	nm	565 ±15	
Range	(McFarland units)	0.3 to 15.0	0.00 to 15.00
Precision		±3%	
Measurement time	sec	1	
Tube diameter	external diameter mm	18	
	with D16 adaptor mm	16	
Sample volume	ml	>2	
Display/display resolution		LED/0.1 McF	LCD/0.01 McF
Independent power supply		-	3 x AA batteries (included with unit)
External power supply		Input AC 120–230V, 50/60Hz Output DC 12V	
Power consumption	230V W	1 (0.08A)	0.1 (0.007A)
	120V W		
Weight	kg	0.7	

PCV series

Options and accessories

		DEN-1	DEN-1B
DEN MCF STDS	Set of liquid McFarland standards in 16mm ø glass tubes. 0.5/1.0/2.0/3.0/4.0 can be decanted into an alternative tube (shelf-life no longer valid). Requires D16 adaptor, supplied with DEN-1/DEN-1B		•
D16	 Spare tube adaptor for tubes with 16mm outer diameter – included as standard		•

Contact us today

Grant Instruments (Cambridge) Ltd
29 Station Road, Shepreth,
Cambridgeshire, SG8 6GB

w. www.grantinstruments.com
t. +44 (0) 1763 260 811
e. salesdesk@grantinstruments.com

► [GrantInstruments](#)
► [GrantInstrument](#)
in [grant-instruments-cambridge-ltd](#)



Find your perfect solution today
Visit our website - www.grantinstruments.com