LABORATORY Digital High -Speed Dispersion Homogenizer

Application in different fields









Medicine

Biochemistry Food and drinks Make ups

Company Information

Guangzhou Yalian is a large-scale company specialized in design, manufacturing, installation and commissioning of daily chemical, chemical, food and pharmaceutical machinery, as well as water treatment equipment. With powerful technical strength, complete inspection facilities, unique and advanced technique as well as great varieties of products, the enterprise strictly implements ISO9001 standard management.

Different Models Parameters

| Model | YFJ200 | YFJ200-SH | YFJ300-SH | | |
|-------------------------|---------------|---------------|---------------|--|--|
| Voltage | AC220V50HZ | | | | |
| Input Power | 280W | 280W | 510W | | |
| Output power | 200W | 200W | 300W | | |
| Working mode | Intermittent | Intermittent | Intermittent | | |
| Speed range | 300-23000rpm | 300-23000rpm | 300-18000rpm | | |
| Working heads thickness | Φ12Φ18 | Φ12Φ18 | Φ28Φ36 | | |
| Mixing capacity | 2-1500ml | 2-1500ml | 500-13000ml | | |
| Exterior Dimension | 250*350*600mm | 250*350*600mm | 250*350*600mm | | |



| Heads | 12G | 18G | 28G | 36G |
|----------------------------------|-----------|-----------|------------|-------------|
| Capacity | 30-800ml | 50-1500ml | 100-8000ml | 150-13000ml |
| Suitable viscosity | 1000mpa.s | 2000mpa.s | 6000mpa.s | 7000mpa.s |
| Rotor line speed | 11s/m | 15s/m | 19s/m | 27s/m |
| Immersion in liquid height | 25/85mm | 30/120mm | 60/155mm | 60/160mm |
| Stator diameter | ф12 | ф18 | ф28 | ф36 |
| Working head length | 150mm | 190mm | 235mm | 240mm |
| Operating temperature | 120°C | 120°C | 120°C | 120°C |
| Work head material | SS304 | SS304 | SS304 | SS304 |
| Working head bearing material | PTEE | PTEE | PTEE | PTEE |













