



SPE100/200/400

Automatic Solid Phase Extraction

Shanghai Sineo SPE100/200/400 automatic solid phase extraction series adopts highly integrated pipeline design, with multi-function sample needle, relying on precise and flexible mechanical arm to improve sample preparation efficiency and bring you convenient and easy working experience , Let your work be faster.

Characteristics

- The injection needle and the extraction column are sealed by a universal plug sealing structure and equipped with H-axis pressing block to ensure good sealing.
- The suspension structure is adopted in the test tube bracket, which ensures the positioning accuracy of the manipulator to the greatest extent.
- The instrument standard router can be connected by WiFi or network line, which fully realizes the whole process of automation and unattended.
- Using modular design, only one communication line and pipeline can work between modules, and it is convenient to replace and maintain.
- Add emergency stop button, when the instrument is abnormal, manual operation can be emergency stop, to maximize user safety.
- Handwheel adjusting origin greatly saves the time of adjusting origin.



Main features

Channel number and control mode:The main machine of the instrument adopts modular design, supports the number of upgrade channels on site, and supports more than 1/2/4/6/8 channels combination.

Continuous processing capacity:Maximum continuous processing capacity of 64-bit samples.

Robot arm:X/Y/Z three-dimensional manipulator design, X/Y axis linkage, improve operational efficiency; H axis is added to move the slider, giving consideration to flexible movement and accurate positioning.

The origin of the handwheel regulating test tube holder is as follows:The origin handwheel adjustment of the test tube holder improves the efficiency of the origin adjustment.

Sample pump: Sampling accuracy, solvent corrosion resistance, high pressure resistance, and compatible with size and volume sampling.

Sample needle: Core accessories, highly integrated functions, can be used for liquid channels, gas channels, but also for extraction column sealing.

Puncture sampling: Sample needle can be selected to realize puncture sampling and avoid sample volatilization loss.

Sample volume and receiving volume: The whole system supports 10/20mL sample tube, 50mL and larger specification customization within two channels, 10mL standard receiving volume and 50mL customization within two channels.

Pressure sensing: Each channel is equipped with a standard pressure sensor, the push-column pressure is closed-loop controlled, and has the functions of overpressure alarm and termination of the experiment.

Velocity control: The top of each extraction column is equipped with an independent sealing cap. The high pressure sealing is realized by docking with the sample needle and moving Z-axis pressure block. The solution passes through the extraction column according to the set flow rate to ensure good reproducibility and parallelism.

Solvent management system: Supporting 8 reagents; Supporting the hint function of insufficient residual capacity; Supporting liquid level following function.

Infiltration and incubation: When the active solvent or eluting solvent is loaded into the extraction column, the liquid level can be kept above the packing for a certain time to ensure full activation or elution and to ensure the ideal experimental results.

Cleaning mode: Supporting various cleaning modes to ensure that the inner and outer walls of sample needles are clean without cross-contamination.

Waste discharge passage: Support environmental protection to recover waste liquor and separate treatment of waste liquor with different properties.

Specification of extraction column: Compatible with conventional 3/6mL extraction column, other specifications of extraction column can be customized according to requirements.

Multi-scheme extraction: Supporting the simultaneous operation of different specifications of extraction columns and different treatment projects without waiting, improving the efficiency of continuous treatment.

A/B column extraction: Support multi-mode tandem column extraction, automatic identification of A/B column extraction scheme.

Online drying/dewatering: Supporting on-line nitrogen purge mode.

Online Concentration: Supporting in-situ nitrogen purge and concentration, the concentration time can be edited, and the assistant concentration and volume setting can be realized automatically.

Large volume injection: Supports the continuous and smooth loading of more than 500 mL samples without interruption, particle wear resistance, corrosion resistance, no need for any consumables and regular maintenance; supports the continuous switching of samples, the number of samples larger than 48 bits.

Cloud services: Supporting upload and download programs and parameters; Supporting online technical support and exchange; Supporting remote monitoring.

Booking starts: After editing the experimental scheme, the start-up time can be self-booked according to the time of the analyzer.

Count down: After the beginning of the experiment, the countdown time is used to facilitate the control of the end time of the experiment and to match the time of the analyzer in advance.

Intelligent self-check and alarm: After the parameter setting is completed, the software self-checks whether there are logic errors, promptly reminds the modification; Intelligent fault alarm system, according to the fault level, chooses to continue or stop.

Technical index

	SPE100	SPE200	SPE400	SPEX00 (Customization)
Channels	1	2	4	X
Channel Independent Control	Support			
Sample pump	Precision Continuous Sample Pump			
Pump flow rate	0-250mL/min			
Types of solvents	8Seed, 500 mL Solvent Bottle			
Sample volume	0.1mL-500L			
Sample tube volume	10mL,20 mL,customization			
Receiving volume	10mL, other specifications customized			
Puncture sampling	Supporting, Specialized Sample Needles and Test Tubes			
Loading mode	X/Y/Z Three-Dimensional Manipulator			
Accuracy of manipulator	0.01mm			
Sealing technology	Docking Technology of Independent Seal Cover and Pan-plug Seal			
Extraction mode	Positive pressure extraction			
column pressure	8-145psi			
Pressure sensing	Support, Overvoltage Alarm, Threshold Editable (0.5-10Bar)			
Column drying method	Nitrogen purge			
Waste collection	Branch collection			
String string	Support, A/B Pillar			
Cleaning mode	Nitrogen purge, solvent cleaning, blowing stirring cleaning and other modes are used to clean the inner and outer walls of sample needles.			
Liquid level following	Support			
Solvent Residual Capacity	Solvent deficiency hints			
Environmental parameters				
Host Size (H*W*D)	680 mm x 560 mm x 650 mm			
Voltage	220V 50Hz			
working temperature	5-40Temperature			
Working humidity	0-90% without condensation			
power	60W	100W	150W	<200W